

# Technical Specifications

## Blocking module

Parameter	Value
Frequency range of control radio signals, GHz	2.4
Type of control code	dialogue
Maximum coverage range	up to 10 meters (*)
Ingress Protection	IP67
Supply Voltage, V	9-16
Consumption current with switched-off ignition, mA	<ul style="list-style-type: none"><li>• 6.6 (i95, i95 LUX)</li><li>• 2.4 (i95 ECO)</li></ul>
Consumption current with switched-on ignition, mA	6.8 (**)
Maximum current load via relay contacts, A	10
Maximum current load at hood lock outputs, A	20
Operating temperature range, °C	from -40 to +125

(\*) — depends on location of the immobilizer components

(\*\*) — with engine blocking inactive

## Indication module

Parameter	Value
Frequency range of control radio signals, GHz	2.4
Type of control code	dialogue
Maximum coverage range	up to 10 meters (*)
Ingress Protection	IP67
Supply Voltage, V	9-16
Consumption current with switched-off ignition, mA	0.01
Operating temperature range, °C	from -40 to +85

(\*) — depends on location of the immobilizer components

# Tag

Parameter	Value
Frequency range of control radio signals, GHz	2.4
Type of control code	dialogue
Maximum coverage range	up to 10 meters (*)
Ingress Protection	IP67
Supply Voltage, V	3.3
Operating temperature range, °C	from −20 to +70
Battery type	CR2025, CR2032
Battery life time	up to 12 months

(\*) — depends on location of the immobilizer components

---

Версия #2  
Admin создал 8 мая 2024 16:36:22  
Admin обновил 10 мая 2024 11:43:27